


DTI ATLAS FIBER ANALYZER TUTORIAL

Berger Jean-Baptiste jean-baptiste.berger@cpe.fr






Introduction ------3

Step I: Select your Data ----- 6


Step 2: Atlas Settings ----- 13







Introduction








Introduction Main Goals

- Statistical analysis of fibers for different cases
- Visualization of those statistics

- After statisticians processing, merging of statistics with fibers
- Visualization on Slicer





Introduction

Pipeline



- Generate Statistics
- Plot Statistics

Statistician

Clean up statistics





- Merge statistics with fibers
- Viewable on slicer



Step I : Select your Data








Select your Data

 In this step, you will specify the data which you want to analyze

 Basically, you will specify a .NRRD file and optionally a Deformation Field






From those files, information will be mapped with an Atlas
 Fiber



There are 2 different ways to select relevant data:

- Manually thanks to this tools help
- ➤ Automatically by opening a data file through the file menu on the top of the window — For more information see "Automated required filling information" beginning at slide 36






Select your Data


Define a CSV File

I- Load an existing .csv file using the browser "..." button

Or

- 2- Create a new empty table by choosing the number of row and column
- 3- Modify the current .csv file You can add a row or a column for the next Id. Or delete a selected row or a selected column
- 4- Finally Save or Delete the current table









Select your Data

Define each column

- Select the type of data that will contains each column
- When you enter a number the
 - associated column will be colored as follow:
 - Orange for optional case names
 - Green for Data
 - Blue for optionalDeformation Fields
- Select whether you will be using h-fields or displacement fields as deformation fields










Select your Data Fill the Table

- Double click on a Data Cell to open a browser and select an image file (.nhdr or .nrrd)
- Double click on a Deformation Cell to open a browser if you want to add a deformation field
- To specify a case name just enter a name in the "Name" column


| | 1 | eformation fie | Name | |
|---|-------------|----------------|-------|--|
| 1 | ampdti.nhdr | deformation | Test | |
| 2 | ampdti.nhdr | deformation | Test1 | |






Select your Data Going to Step 2

- To go to the next step you need to specify an output folder (see Output Hierarchy for more information)
- If there are:












Step 2: Atlas Settings







Atlas Settings

 Here you will choose which Atlas Fiber you want to map your data with

This step will extract the fiber from the input image











Atlas Settings Specify the Atlas Folder

- Click on "..." button to open the browser
- Specify the path to your Atlas Folder



This tool only support VTK Files or FIB Files






Atlas Settings Select Fibers to use

- On the left part you can see every Fibers File read on the Atlas Folder
- The right part contains the fibers that you chose to continue the analysis
- Click on a fiber to select it
- Use ">>" or "<<" buttons to send a selected item to the right or left part.
- "Add All" and "Remove All" will send every fibers from the left to the right and vice versa







Atlas Settings

Extract Fiber From Volume

- If there is at least one fiber selected, you can click on "Apply"
- "Apply" will process data for each cases and for each selected fibers
- It will create a VTK File for each combination case-fiber named as following: casename_fibername.vtk

You can see created file on


eformation fie

2 ...ampdti.nhdr ...deformation Test1


...deformation Test

1 ...ampdti.nhdr

Name







Genu.vtk

...erAnalyzer-

...erAnalyzer-


ILF-Right.vtk


...erAnalyzer-

...erAnalyzer-



- If a file already exist in the same folder (see Output Hierarchy) a window pop up
- "Cancel" will stop FiberProcess
- "No" and "No to All" will replace the existing file by the computed one(s)
- "Yes" and "Yes to All" will use the existing file(s) for the following steps









Atlas Settings Going to Step 3

 If processing went right, "Next Step" button will replace the "Apply" button

 Clicking on "Next Step" will send you to Step 3










Step 3: Analysis Settings








- In this step you will read statistical information from the previous extracted fiber
- An initialization will be done thanks to a plan file
- All those information will be gathered in one data sheet per cases

 Besides cases, those information will also be extracted from the Atlas Fiber to allow you to compare both files from case and atlas








Analysis Settings Select planes

- Listed planes are FVP File read in the atlas directory
- Click to select or deselect a plane file
- A plane file should contains the name of the fiber to be read
- If no plane file is selected for a fiber, the tool will use an auto plane setting











Analysis Settings Select parameters

 Select which parameters you want to compute

 At least one parameter needs to be checked









Analysis Settings Select summary reports layout

- Gathered information (CSV Format) will be written as follow:
 - ➢ If you select "Arc length : row", one data sample will correspond to one line and one case for one column
 - If you select "Case : row", the table will be transposed

Summary reports

- Arc lenght : row / Case : column
- Case : row / Arc lenght : column








- This option will define the origin point of an auto plane
- If "Center of Gravity" is checked, the origin will be the center of gravity of the whole fiber bundle
- If "Median point on Fiber" is checked, the origin will be the median point on the fiber
- The normal is always the direction between the two closest point to the origin

Auto Plane Origin Options

- O Center of Gravity
- Median point on Fiber







- As in Step 2, click on the "Apply" button to calculate statistics and gathered information on a CSV File
- It will calculate statistics for each file created on Step 2
- One FVP File per call will be created and added in the Table plus one per fiber that will describe the atlas
- Gathered informations files are created as follow:
 - > One file per fiber per parameter is created
 - > Each file is named : fibername_parameter.csv
- When computation is finished, the "Next Step" button will replace the "Apply" button
- Click on "Next Step" to go to the Step 4


| 15 | 1 | eformation fie | Name | Genu.vtk | ILF-Right.vtk | Genu.fvp | ILF-Right.fvp |
|----|-------------|----------------|-------|-------------|---------------|-------------|---------------|
| 1 | ampdti.nhdr | deformation | Test | erAnalyzer- | erAnalyzer- | erAnalyzer- | erAnalyzer- |
| 2 | ampdti.nhdr | deformation | Test1 | erAnalyzer- | erAnalyzer- | erAnalyzer- | erAnalyzer- |








Step 4: Plot Window







- This step helps you to compare statistical information by plotting them
- 3 types of curves can be distinguished: curves from cases, from atlas and statistical values such as mean and std
- You also will be able to check the correlation mapping between each cases and the atlas









Pop up the Plot Window

- The list shows which files will be plotted
- Only FVP Files can be read
- Click on "Plot" to open the plot window that will display each relevant curves








Window structure

- Plot Interface: Checked curves will be displayed here. Three kind of curves can be displayed:
 - Cases
 - > Atlas
 - > Statistic
- Detailed information of the FVP File read
- Option panel to change the display









Selecting displayed curves

- Choose which parameter to display for each curves
- Then, Check a box corresponding to a case to display the associated curve
- Choose the fiber you want to display
- Just one parameter and one fiber can be selected at a time
- Standard deviation curves are plotted with discontinue dashes











Adapting pixel size

 Use Sliders to change the pixel size for each type of curves

Pixel width "I" is set as default











Configure axes scales

This is where you can set the axis scales

 The Plot will be updated each time you finished entering a number



 Click on "Auto Scale" button to auto set the values depending on plotted curves







Get correlation coefficients

- Each Case curves have a correlation coefficient with the Atlas curve
- If the correlation between a curve and the atlas is below the correlation threshold this curve will be colored in red
- Colors on curves correspond to colors on case names
- Click on "Correlation check mapping" to display all of the correlation coefficients and color each curves depending on the coefficient: (Light grey for I and black for 0)











Additional Information







Merging Statistic With Fiber Data







 This tool will use a data sheet to merge data in the original .vtk file of a fiber

 This will allow you to display each parameter value distribution in Slicer

 For instance, you will be able to see the 'Fa' distribution as a color map on the fiber







Merge Stat With Fiber

Specifying arguments

- Choose a CSV File containing data samples to merge
- Choose a VTK File for the data samples to be merged with
- Specify the name of the VTK Output File
- Choose Min and Max values of the linear interpolation that will computes Slicer data








Merge Stat With Fiber

Calling MergeStatWithFiber

- Required fields:
 - CSV Input File
 - > VTK Input File
 - Output Filename
- Optional field : Interpolation values
- Click on Parametrization and the result will be written on the Output Filename










Output Hierarchy





Output Hierarchy


Output Folder/

Cases/

/CaseNames → Here will be stored Cases VTK Files and Statistics FVP Files for associated Case named: casename_fibername.vtk or .fvp

- Fibers/ → Here will be stored Statistics from Atlas VTK File for associated
 Fiber named : fibername.fvp
- FiberProfiles/

FiberNames → Here will be stored gathered information for associated parameter named :
parametername_fibername.csv







Automated Required Information Filling







- There is two types of information files:
 - ➤ Data File: This one will fill information required for the first step such as the CSV File name
 - Analysis File: This one will fill information required for Step 2 and Step 3 such as desired parameters
- The global structure is:
 - ➤ A beginning line
 - ➤ List of Key :Value
- You can add commentaries by beginning a line by "#"
- Listed values should be separated with a coma
- A default Analysis File will be created at the tool first use. Feel free
 to modify it since it will be loaded automatically for next uses. This
 default file located in the Output Folder is called:
 Default_Analysis_Parameters.txt
- Use the file menu to Save or Load those different files





Automated Required Information Filling Writing a Data File

- The first line must be :"Data parameters for DTIAtlasFiberAnalyzer :"
- Then, you can specify each of the following (Order doesn't matter):
 - > "CSVFile:" + Path to the CSV File name
 - ➤ "Data Column:", "Deformation Field Column:" or "Case Column:" + number of the designated column
 - Field Type: "+ "h-field" or "displacement field" describing the deformation fields you will be using
 - "Output Folder:" + Path to the chosen output folder name

Example :

Data parameters for DTIAtlasFiberAnalyzer:

CSVFile:/path/to/CSV/File.csv

Data Column: I

Deformation Field Column : 2 Field Type : displacement field

Case Column: 3

Output Folder : /path/to/Output/Folder





Automated Required Information Filling Writing an Analysis File

- The first line must be : "Analysis parameters for DTIAtlasFiberAnalyzer :"
- Then, you can specify each of the following (Order doesn't matter):
 - > "Atlas Fiber Folder:" + Path to the Atlas Folder
 - "Selected Fibers:" + Name of each Fiber Files (in the Atlas Folder)
 - "Selected Planes: " + Name of each Plane Files (in the Atlas Folder)
 - "Profile parameter:" + Name of each Parameters
 - > "Col and Row:" + Either "Case in row" or "Case in col" to transpose or not the gathered information table
 - "Auto Plane Origin: " + Either "median" or "gravity"

Example:

Analysis parameters for DTIAtlasFiberAnalyzer:


Atlas Fiber Folder : /path/to/Atlas/Folder

Selected Fibers : Genu.vtk, ILF-Right.vtk

Selected Planes : Genu.fvp Profile parameter : fa,md,fro

Col and Row : Case in row

Auto Plane Origin : median







Contributors

- Jean-Baptiste Berger : jean-baptiste.berger@cpe.fr
- Benjamin Yvernault : <u>benjamin.yvernault@cpe.fr</u>
- Yundi Shi : yundiuu@gmail.com
- Clement Vachet : <u>cvachet@unc.edu</u>
- Martin Styner :
 <u>martin_styner@ieee.org</u>



